

WBCS3000K8

8 Channel Battery Test System



- *±1A current over 3 current ranges*
- *Applied voltage range of ±5V*
- *Potentiostat/Galvanostat circuit*
- *High accuracy*
- *Sampling time of 10msec*
- *Plugin channels for easy maintenance*
- *LAN communication*

Battery Charge/Discharge Test System for standard application

The 8 channel battery test system, **WBCS3000K8**, is designed for general practices when researching materials to optimize battery performance. As a spin-off of WBCS3000S, the **WBCS3000K8** has the same features as WBCS3000S but the channel expansion of **WBCS3000K8** is not available.

The **WBCS3000K8** has a current control range of 10mA to 1A and voltage range of -5V to +5V as standard. The accuracy for current and voltage on these channels is $\pm 0.02\%$ FSR. The sampling time is 10msec.

The **WBCS3000K8** does not only support various techniques for battery studies, but also carries out electrochemical techniques such as corrosion test techniques, electro-analytical techniques, cyclic voltammetry, chronoamperometry, and potentiometry, etc. and this feature allows user to perform general Echem experiments.

The Smart Interface(SI) software is a convenient and powerful tool allowing:

- easily making schedule files by using schedule editor
- selecting pre-defined techniques
- classifying/grouping channels by user's purpose
- monitoring detailed test data
- providing general/cycle graph format
- converting the data to ASCII or excel format

The **WBCS3000K8** is supplied with eight cell cables and can communicate with the computer by the way of a Local Area Network(LAN).

● Features

- Potentiostat/Galvanostat circuit : no time delay between the charge and discharge cycles
- Supports techniques for battery studies such as CC/CV test, CC/CC test, CV test, as well GITT/PITT test for calculation of diffusion coefficient.
- The various safety functions are provided to protect the cell and system from being damaged.
- The obtained data can be analyzed by IVMAN™ software without license code for further analysis.

● For Energy Test

- Charge/Discharge(CC/CV) Test
- Constant Current Charge/Discharge(CC/CC) Test
- IV Curve Test
- Electrochemical Voltage Spectroscopy(EVS) Test
- Galvanostatic Intermittent Titration Technique(GITT) Test
- Potentiostatic Intermittent Titration Technique(PITT) Test
- Cyclic Voltammetry
- Potentiostatic Experiment With Half Cell

● Options

- Battery Jig
- Coin Cell Holder
- Test Cell
- Dilatometer

● Specifications

Control voltage range	±5V
Control current range	1A, 3 ranges
LED	Run: 1ea, Mode: 2ea
Input impedance	10 ¹⁰ Ohm
Cell connection	4 probe type, alligator clip cables
No. of channels	8
Slew rate	1V/usec
Voltage accuracy	±0.02% f.s.
Current accuracy	±0.02% f.s.
Voltage Control/Measurement	
Full scale ranges	±5V
Resolution(16 bits)	0.15mV
Current Control/Measurement	
Full scale ranges	Max. 1A@5V
Resolution	16 bit(0.0015% f.s)
Communication	TCP/IP
Sampling time	10msec

All specifications are subject to change without notice.



WonATech Co., Ltd.
7 Neunganmal 1-gil, Seocho-gu,
Seoul, 06801, Korea
Tel: +82-2-578-6516 Fax: +82-2-576-2635
e-mail: sales@wonatech.com
website: www.wonatech.com

Local Distributor