

WMPG1000K8

8 Channel Potentiostat Galvanostat



- *Fixed specification*
- *Perfect for general electrochemical tests*
- *$\pm 1A$ current over 5 current ranges*
- *Applied voltage range of $\pm 10V$*
- *4 Kelvin probe type P'stat/G'stat circuit*
- *High accuracy*
- *Sampling time of 10msec*
- *Plugin channels for easy maintenance*
- *LAN communication*

8 Channel Potentiostat/Galvanostat for standard application

The 8 channel potentiostat/galvanostat, **WMPG1000K8**, is designed for general purpose electrochemical experiments and its versatile features allow users to perform a wide range of electrochemical research and development. As a spin-off of WMPG1000S, the **WMPG1000K8** has the same features as WMPG1000S but the channel expansion of **WMPG1000K8** is not available.

The **WMPG1000K8** has a current control range of 100uA to 1A and voltage range of -10V to +10V as standard. The accuracy for current and voltage on these channels is $\pm 0.01\%$ FSR. The sampling time is 10msec.

The **WMPG1000K8** does not only support various electrochemical techniques such as corrosion test techniques, electro-analytical techniques, cyclic voltammetry, chronoamperometry, and potentiometry, etc. but also carries out experiments on batteries. This feature allows user to perform general Echem experiments.

The Smart Interface(SI) software is a convenient and powerful tool allowing:

- easily making schedule files by using schedule editor
- selecting pre-defined techniques
- classifying/grouping channels by user's purpose
- monitoring detailed test data
- providing general/cycle graph format
- converting the data to ASCII or excel format

The **WMPG1000K8** is supplied with eight cell cables and can communicate with the computer by the way of a Local Area Network(LAN).

● Features

- Multiple current ranges for improved accuracy over a wide range of testing conditions.
- High resolution 16 bit DAC/ADC for system control and data acquisition.
- Supports techniques for battery studies such as CC/CV test, CC/CC test, CV test, as well GITT/PITT test for calculation of diffusion coefficient.
- High sampling rate.
- The various safety functions are provided to protect the cell and system from being damaged.
- The obtained data can be analyzed by IVMAN™ software without license code for further analysis.

● For Electroanalytical Measurement

- Cyclic voltammetry
- Linear sweep voltammetry
- Chrono-amperometry
- Chrono-coulometry
- Chrono-potentiometry

● Corrosion Measurement

- Tafel plot
- Potentiodynamic
- Potentiostatic
- Galvanostatic
- Cyclic polarization
- Ecorr vs. time
- Linear polarization resistance

● For Energy Test

- Charge/Discharge(CC/CV) Test
- Constant Current Charge/Discharge(CC/CC) Test
- Steady state CV
- Pstat IV curve
- Gstat IV curve
- Electrochemical Voltage Spectroscopy(EVS) Test
- Galvanostatic Intermittent Titration Technique(GITT) Test
- Potentiostatic Intermittent Titration Technique(PITT) Test

● Specifications

Control voltage range	±10V
Compliance voltage	±12V
Control current range	1A, 5 ranges
LED	Run: 1ea, Mode: 2ea
Input impedance	10 ¹² Ohm
Cell connection	4 probe type, alligator clip cables
No. of channels	8
Voltage accuracy	±0.02% f.s.
Current accuracy	±0.02% f.s.
Voltage Control/Measurement	
Full scale ranges	±10V
Resolution(16 bits)	0.3mV
Current Control/Measurement	
Full scale ranges	Max. 1A@10V
Resolution	16 bit(0.0015% f.s)
Communication	TCP/IP
Sampling time	10msec

All specifications are subject to change without notice.



WonATech Co., Ltd.
7 Neunganmal 1-gil, Seocho-gu,
Seoul, 06801, Korea
Tel: +82-2-578-6516 Fax: +82-2-576-2635
e-mail: sales@wonatech.com
website: www.wonatech.com

Local Distributor