

WMPG1000D Series

Dual Channel Potentiostat/Galvanostat Module



- For Mid power applications
- Max 400Watt
- 5 current ranges
- Applied voltage range of Max $\leq \pm 40V$
- 4 Kelvin probe type P'stat/G'stat circuit
- High accuracy
- Max 128 channels configuration
- Independent power supply per dual channel
- LAN communication

Mid Power Potentiostat/Galvanostat channel for power application

The mid power potentiostat/galvanostat channel, **WMPG1000D**, is designed for Mid power purpose electrochemical experiments and its versatile features allow users to perform a wide range of electrochemical research and development. The **WMPG1000D series** requires external 8channel controller and the channel power limit is 400Watt.

The **WMPG1000D series** can be configured with custom specification not exceeding its maximum power (400Watt), voltage limitation($\leq \pm 40V$).

Typical models for WMPG1000D are

- -10V to 10V @ 20Amp **WMPG1000D_1020B**
- -20V to 20V @10Amp **WMPG1000D_2010B**

Dual channel module has its own power supply.

Optional accessories for this system is auxiliary voltage measurement and temperature measurement

The **WMPG1000D series channel** can support various application such as corrosion, physical electrochemistry, electrosynthesis, electrolysis, electroplating and experiments on energy devices.

The Smart Interface(SI) software for WMPG multichannel potentiostat/galvanostat is a convenient and powerful tool allowing:

- easily making schedule files by using schedule editor
- selecting pre-defined techniques
- classifying/grouping channels by user's purpose
- monitoring detailed test data
- providing general/cycle graph format
- converting the data to ASCII or excel format

The **WMPG1000 series** can communicate with the computer by the way of a Local Area Network(LAN).

● Features

- current ranges for improved accuracy over a wide range of testing conditions.
- High resolution 16 bit DAC/ADC for system control and data acquisition.
- Supports techniques for battery studies such as CC/CV test, CC/CC test, CV test, as well GITT/PITT test for calculation of diffusion coefficient.
- High sampling rate.
- The various safety functions are provided to protect the cell and system from being damaged.
- The obtained data can be analyzed by IVMAN™ software without license code for further analysis.

● For Electroanalytical Measurement

- Cyclic voltammetry
- Linear sweep voltammetry
- Chrono-amperometry
- Chrono-coulometry
- Chrono-potentiometry

● Corrosion Measurement

- Tafel plot
- Potentiodynamic
- Potentiostatic
- Galvanostatic
- Cyclic polarization
- Ecorr vs. time
- Linear polarization resistance

● For Energy Test

- Charge/Discharge(CC/CV) Test
- Constant Current Charge/Discharge(CC/CC) Test
- Steady state CV
- Pstat IV curve
- Gstat IV curve
- Electrochemical Voltage Spectroscopy(EVS) Test
- Galvanostatic Intermittent Titration Technique(GITT) Test
- Potentiostatic Intermittent Titration Technique(PITT) Test

● Specifications

Control voltage range	Max $\leq \pm 40V$
Compliance voltage	Depending on control voltage
Control current range	5 ranges
LED	Run: 1ea, Mode: 2ea, Irange:5 ea
Input impedance	10^{12} Ohm
Cell connection	4 probe type, alligator clip cables
No. of channels	2 per module
Voltage accuracy	$\pm 0.05\%$ f.s.
Current accuracy	$\pm 0.05\%$ f.s.
Voltage Control/Measurement	
Full scale ranges	Max $\pm 40V$
Resolution(16 bits)	0.0015% f.s
Current Control/Measurement	
Full scale ranges	Max. f.s under 400Watt
Resolution	16 bit(0.0015% f.s)
Communication	TCP/IP
Sampling time	- 8~16 channel system : 20msec - 17~32 channel system : 25msec - 33~128 channel system : 50msec

All specifications are subject to change without notice.



WonATech Co., Ltd.
7 Neunganmal 1-gil, Seocho-gu,
Seoul, 06801, Korea
Tel: +82-2-578-6516 Fax: +82-2-576-2635
e-mail: sales@wonatech.com
website: www.wonatech.com

Local Distributor