

# WMPG1000Le

## Low Current Multichannel Potentiostat/Galvanostat



- *For low power applications*
- *Perfect for corrosion test*
- *$\pm 100\text{mA}$  current over 5 current ranges*
- *Applied voltage range of  $\pm 10\text{V}$*
- *4 Kelvin probe type P'stat/G'stat circuit*
- *High accuracy*
- *Max 64 channels configuration*
- *Plugin channels for easy maintenance*
- *LAN communication*

### MultiChannel Potentiostat/Galvanostat for low current application

The multichannel potentiostat/galvanostat, **WMPG1000Le**, is designed for low current applications and it is especially suitable for corrosion test.

The **WMPG1000Le** has a current control range of  $10\mu\text{A}$  to  $100\text{mA}$  and voltage range of  $-10\text{V}$  to  $+10\text{V}$  as standard. The accuracy for current and voltage on these channels is  $\pm 0.02\%$  FSR. Max channel configuration is 64 per one PC.

The **WMPG1000Le** does not only support various electrochemical techniques such as corrosion test techniques, electro-analytical techniques, cyclic voltammetry, chronoamperometry, and potentiometry, etc. but also carries out experiments on batteries. This feature allows user to perform general Echem experiments.

The Smart Interface(SI) software is a convenient and powerful tool allowing:

- easily making schedule files by using schedule editor
- selecting pre-defined techniques
- classifying/grouping channels by user's purpose
- monitoring detailed test data
- providing general/cycle graph format
- converting the data to ASCII or excel format

The compact size **WMPG1000Le** can communicate with the computer by the way of a Local Area Network(LAN).

## ● Features

- Multiple current ranges for improved accuracy over a wide range of testing conditions.
- High resolution 16 bit DAC/ADC for system control and data acquisition.
- Provides various techniques for corrosion study.
- Supports techniques for battery studies such as CC/CV test, CC/CC test, CV test, as well GITT/PITT test for calculation of diffusion coefficient.
- High sampling rate.
- The various safety functions are provided to protect the cell and system from being damaged.
- The obtained data can be analyzed by IVMAN™ software without license code for further analysis.

## ● For Electroanalytical Measurement

- Cyclic voltammetry
- Linear sweep voltammetry
- Chrono-amperometry
- Chrono-coulometry
- Chrono-potentiometry

## ● Corrosion Measurement

- Tafel plot
- Potentiodynamic
- Potentiostatic
- Galvanostatic
- Cyclic polarization
- Ecorr vs. time
- Linear polarization resistance

## ● For Energy Test

- Charge/Discharge(CC/CV) Test
- Constant Current Charge/Discharge(CC/CC) Test
- Steady state CV
- Pstat IV curve
- Gstat IV curve
- Electrochemical Voltage Spectroscopy(EVS) Test
- Galvanostatic Intermittent Titration Technique(GITT) Test
- Potentiostatic Intermittent Titration Technique(PITT) Test

## ● Specifications

Control voltage range	±10V
Compliance voltage	±12V
Control current range	100mA, 5 ranges
LED	Run: 1ea
Input impedance	10 <sup>12</sup> Ohm
Cell connection	4 probe type, alligator clip cables
Max channels	64
Voltage accuracy	±0.02% f.s.
Current accuracy	±0.02% f.s.
<b>Voltage Control/Measurement</b>	
Full scale ranges	±10V
Resolution(16 bits)	0.3mV
<b>Current Control/Measurement</b>	
Full scale ranges	Max. 100mA@10V
Resolution	16 bit(0.0015% f.s)
Communication	TCP/IP
Sampling time 16channels/SIF	- Without option (Max 64 channels): 10msec - With option (AuxV and/or Temperature input) (Max 32 channels): 10msec
Size	W350.2xD328.1xH83.6mm

All specifications are subject to change without notice.



WonATech Co., Ltd.  
7 Neunganmal 1-gil, Seocho-gu,  
Seoul, 06801, Korea  
Tel: +82-2-578-6516 Fax: +82-2-576-2635  
e-mail: sales@wonatech.com  
website: www.wonatech.com

Local Distributor